



Specifications

| | |
|----------------------------|----------------------------|
| Input Voltage | 24V DC / 230V AC |
| Wattage | 8 W |
| Operating Temp | 0-70° degree |
| Luminaire | SMD LED Strip |
| Control Gear | Onboard |
| CRI | 82 Typical |
| CCT | 6500K (Cool White) |
| LED make | Edison / Everlight / Osram |
| Lumens | 650 Lm |
| Light Viewing Angle | 120° |
| Protection Grade | IP54 |
| Lamp Head | Aluminium |
| Arms | M.S. Powder Coated |
| Weight | 2.0 Kg Approx. |
| Average Lifespan | 30,000 Hrs |

Features

- Ideal for Machines & Equipment's requiring high light output LED's
- CE Certified
- Lamp with high grade components & excellent Cool Day Light illumination
- M.S. Powder Coated Foldable Arms
- Adjustable Arms & Head for positioning
- Rugged in construction
- Heat resistant & shock proof & easily mountable either vertically or horizontally
- Stringently checked on various criterion of performance
- Longer functional life & Cost Effective
- Modular design with Superior Finishing & tamperproof packaging
- Widely used in automobile, Production & Electrical Engineering industries

Ordering Code

| Internal Ballast Model | Voltage | Wattage |
|------------------------|---------|---------|
| SMC-8ES2- 24 LED | 24V DC | 8W |
| SMC-8ES2-230 LED | 230V AC | 8W |