



## Specifications

<b>Input Voltage</b>	24V DC / 230V AC
<b>Wattage</b>	9 W
<b>Operating Temp</b>	0-70° degree
<b>Luminaire</b>	SMD LED Strip
<b>Control Gear</b>	Onboard
<b>CRI</b>	82 Typical
<b>CCT</b>	6500K (Cool White)
<b>LED make</b>	Edison / Everlight / Osram
<b>No. Of. LED's</b>	16
<b>Lumens</b>	850 Lm
<b>Light Viewing Angle</b>	120°
<b>Protection Grade</b>	IP54
<b>Lamp Head</b>	Aluminium
<b>Arms</b>	M.S. Powder Coated
<b>Weight</b>	2.0 Kg Approx.
<b>Average Lifespan</b>	30,000 Hrs

## Features

- Ideal for Machines & Equipment's requiring high light output LED's
- CE Certified
- Lamp with high grade components & excellent Cool Day Light illumination
- M.S. Powder Coated Foldable Arms
- Adjustable Arms & Head for positioning
- Rugged in construction
- Heat resistant & shock proof & easily mountable either vertically or horizontally
- Stringently checked on various criterion of performance
- Longer functional life & Cost Effective
- Modular design with Superior Finishing & tamperproof packaging
- Widely used in automobile, Production & Electrical Engineering industries

## Ordering Code

Internal Ballast Model	Voltage	Wattage
SMC-9ES3- 24 LED	24V DC	9W
SMC-9ES3-230 LED	230V AC	9W

