



## Specifications

<b>Input Voltage :</b>	24V AC/DC
<b>Operating Temperature</b>	0°C to 70°C
<b>Luminaire</b>	PCB Mounted LED's
<b>LED Power dissipation</b>	72mW
<b>CRI</b>	82 Typical
<b>LED Color</b>	Red / Amber / Green
<b>Functions</b>	Steady / Buzzer
<b>Protection grade</b>	IP 54
<b>Flasher</b>	IC 555 & TIP 127 Transistor
<b>LED operating current</b>	20 mA
<b>Buzzer Current</b>	100 mA
<b>Buzzer Sound</b>	<100 db
<b>Diameter</b>	∅ 95 mm
<b>Average Life Hours</b>	30000 Hrs
<b>Luminous Intensity</b>	<b>Red : 900-1200 mcd    Amber : 400-900 mcd</b> <b>Green : 2000-2200 mcd</b>

## Ordering Codes

### With Buzzer Models

SMC-MB-1-T-1- (R/A/G)-(B/O)                      24V AC/DC

### Without Buzzer Models

SMC-MB-1-T-1- (R/A/G)-(O)                      24V AC/DC

## Features

- Lamp for machine status Indication
- Suitable for machines and equipments in high light output LED's
- CE certified
- ROHS Compliant
- IP 54 grade Protection
- 3 Colors in 1 Lamp (Red, Amber & Green)
- Heat Resistant, shock proof & easily mountable
- Stringently checked on various criterion of performance
- Modular design with superior finishing & tamperproof packaging
- Longer functional life

## Dimensional Drawing

