



Specifications

Operating Temperature
Nominal Operating Voltage
Cable Type-Round
Core
Cable Make
Cable Type-Flat
Flat Cable
Connection

0 to 70 Degree Celsius
 24VDC
 PVC Insulated non shielded
 Multicore
 Lapp / Calender Make
 Ribbon Multi Wire Planner
 Flat Ribbon Connector
 Color Wire Coding

Connection Details

Type of Connections
Make
Terminal Option
Wire Cross Section

FRC wires soldered
 O/E/N
 Plug in
 0.14 sq.mm /
 0.22 sq.mm
 1:1 Electrical Connection
 20, 26, 34, 40, 50, 64

Routing
 FRC Pins

Ordering Code

Model

SMC-CA-1.0-R
 SMC-CH-1.5-R
 SMC-CH-0.75-F
 SMC-CH-1.5-F

ROUND
 ROUND
 FLAT
 FLAT

50 Pin FRC Pin Out

19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1
GND	GND	GND	GND	GND	GND	GND	GND	GND	GND	GND	GND	GND	GND	GND	GND	GND	GND	GND
IO	REQ	C/D	SEL	MSG	RST	ACK	BSY	GND	ATN	GND	GND	TRM	GND	GND	GND	GND	GND	DB0

