



### Specifications

<b>Input Voltage</b>	: 24VDC
<b>Power</b>	: 5W
<b>CRI</b>	: 80
<b>Lamp Luminous</b>	: 100 Lumen
<b>Beam Angle</b>	: 360 degree
<b>Input Current</b>	: R: 50 mA Y: 80 mA G: 30 mA Buzzer: 30 mA
<b>Working Temp</b>	: 0°C to 70°C
<b>IP rating</b>	: IP50
<b>Lamp Body</b>	: Polycarbonate
<b>Body Shape</b>	: Base Ball Bat Shape
<b>Lamp Body Color</b>	: Silver
<b>Colors</b>	: RED, YELLOW, GREEN
<b>Flashing</b>	: Red Color
<b>Foldable</b>	: 90 degree
<b>Average Life</b>	: 50000 Hrs
<b>Installation</b>	: Fixed By Screw

### Ordering Codes

SMC-FI-3-T-1-(R/A/G)-(B/F) 24V DC

### Features

- Machine status Indication
- Suitable for machines and equipments in high light output LED's
- 90 degree Foldable
- Energy saver with IP 50 grade Protection
- Heat Resistant, shock proof & easily mountable
- Ideal for temperature fluctuating situations
- Stringently checked on various criterion of performance
- Modular design with superior finishing & tamperproof packaging
- Longer functional life

### Dimensional Drawing

