Surya

Data Sheet

Rev_1







Specifications

Wattage

Input Voltage 24V DC / 110V AC OR

230V AC 14 W

Operating Temp 0-70° degree

Protection Grade IP67

LuminaireSMD LED StripControl GearOnboardCRI82 Typical

CCT 6500K (Cool White)

LED make Edison / Everlight / Osram

No. Of. LED's 36
Operating Current 0.75 Amp
Lumens 1500 Lm
Light Viewing Angle 120°

Lamp Housing Toughened Glass

Diameter60 mmFasteningEnd BracketsWeight1.5 Kg Approx.

Cable length 3 Mtrs **Average Lifespan** 30,000 Hrs

Features

Ideal for CNC & SPM Machines

CE Certified

Coolant, Water & dust proof hence suitable for wet
 & dry applications

IP67 grade protection

360 degree adjustable viewing angle

 Used good quality Aluminum with excellent anticorrosion and good heat dissipation characteristic

Lamp with high grade components & excellent Cool
 Day Light illumination

 Heat resistant & shock proof & easily mountable either vertically or horizontally

 Stringently checked on various criterion of performance

Longer functional life & Cost Effective

 Modular design with Superior Finishing & tamperproof packaging

 Widely used in automobile, Production & Electrical Engineering industries

Ordering Code

Internal Ballast Model	Voltage	Total Length
SMC-CNC-4-1-I-L	24V DC	515
SMC-CNC-4-2-I-L	110V AC	515
SMC-CNC-4-3-I-L	230V AC	515

Dimensional Drawing



FRONT VIEW



SIDE VIEW

