Surya

Data Sheet

Rev_1







Features

- Ideal for CNC & SPM Machines
- CE Certified
- Coolant, Water & dust proof hence suitable for wet & dry applications
- IP67 grade protection
- 360 degree adjustable viewing angle
- Used good quality Aluminum with excellent anticorrosion and good heat dissipation characteristic
- Lamp with high grade components & excellent Cool
 Day Light illumination
- Heat resistant & shock proof & easily mountable either vertically or horizontally
- Stringently checked on various criterion of performance
- Longer functional life & Cost Effective
- Modular design with Superior Finishing & tamperproof packaging
- Widely used in automobile, Production & Electrical Engineering industries

Specifications

Input Voltage 24V DC / 110V AC OR

230V AC 18 W

Wattage 18 W
Operating Temp 0-70° degree

Protection Grade IP67

Luminaire SMD LED Strip
Control Gear Onboard

CRI 82 Typical

CCT 6500K (Cool White)
LED make Edison / Everlight / Osram

No. Of. LED's 36
Operating Current 0.75 Amp
Lumens 1500 Lm
Light Viewing Angle 120°

Lamp Housing Toughened Glass

Diameter60 mmFasteningEnd BracketsWeight1.5 Kg Approx.

Cable length 3 Mtrs Average Lifespan 30,000 Hrs

Ordering Code

Internal Ballast Model	Voltage	Total Length
SMC-CNC-4-1-I-L	24V DC	515
SMC-CNC-4-2-I-L	110V AC	515
SMC-CNC-4-3-I-L	230V AC	515

Dimensional Drawing



FRONT VIEW



SIDE VIEW



ISO 9001:2015 Certified