



## Specifications

<b>Input Voltage</b>	24V DC / 110V AC OR 230V AC
<b>Wattage</b>	<b>32 W</b>
<b>Operating Temp</b>	0-70° degree
<b>Protection Grade</b>	IP67
<b>Luminaire</b>	SMD LED Strip
<b>Control Gear</b>	Onboard
<b>CRI</b>	82 Typical
<b>CCT</b>	6500K (Cool White)
<b>LED make</b>	Edison / Everlight / Osram
<b>No. Of. LED's</b>	72
<b>Lumens</b>	3500 Lm
<b>Light Viewing Angle</b>	120°
<b>Lamp Housing</b>	Toughened Glass
<b>Diameter</b>	60 mm
<b>Fastening</b>	End Brackets
<b>Weight</b>	2 Kg Approx.
<b>Cable length</b>	3 Mtrs
<b>Lifespan</b>	30,000 Hrs

## Features

- Ideal for CNC & SPM Machines
- CE Certified
- Coolant, Water & dust proof hence suitable for wet & dry applications
- IP67 grade protection
- 360 degree adjustable viewing angle
- Used good quality Aluminum with excellent anti-corrosion and good heat dissipation characteristic
- Lamp with high grade components & excellent Cool Day Light illumination
- Heat resistant & shock proof & easily mountable either vertically or horizontally
- Stringently checked on various criterion of performance
- Longer functional life & Cost Effective
- Modular design with Superior Finishing & tamperproof packaging
- Widely used in automobile, Production & Electrical Engineering industries

## Ordering Code

Internal Ballast Model	Voltage	Total Length
SMC-CNC-6-1-I-L	24V DC	585
External ballast Model		
SMC-CNC-6-2-E-L	110V AC	585
SMC-CNC-6-3-E-L	230V AC	585

## Dimensional Drawing

