Surya

Data Sheet







Features

- Ideal for CNC & SPM Machines
- CE Certified
- Coolant, Water & dust proof hence suitable for wet
 & dry applications
- IP67 grade protection
- 360 degree adjustable viewing angle
- Used good quality Aluminum with excellent anticorrosion and good heat dissipation characteristic
- Lamp with high grade components & excellent Cool
 Day Light illumination
- Heat resistant & shock proof & easily mountab either vertically or horizontally
- Stringently checked on various criterion of performance
- Longer functional life & Cost Effective
- Modular design with Superior Finishing & tamperproof packaging
- Widely used in automobile, Production & Electrical Engineering industries

Specifications

Wattage

Input Voltage 24V DC / 110V AC OR

230V AC **36 W**

Operating Temp 0-70° degree

Protection Grade IP67

Luminaire SMD LED Strip
Control Gear Onboard

CRI 82 Typical

CCT 6500K (Cool White)

LED make Edison / Everlight / Osram

No. Of. LED's 72

Lumens 3500 Lm Light Viewing Angle 120°

Lamp Housing Toughened Glass


Diameter60 mmFasteningEnd BracketsWeight2 Kg Approx.Cable length3 Mtrs

Lifespan 30,000 Hrs

Ordering Code

Internal Ballast Model	Voltage	Total Length
SMC-CNC-6-1-I-L	24V DC	585
External ballast Model		
SMC-CNC-6-2-E-L	110V AC	585
SMC-CNC-6-3-E-L	230V AC	585

Dimensional Drawing





SIDE VIEW