



Specifications

Wattage	5W (+/- 20%)
Input Voltage	90 - 265V AC / 50-60 Hz
Protection Grade	IP54
Working Environment	-30 to 75 degree celsius
Luminaire	SMD LED strip
CRI	82 Typical
LED color (CCT)	Cool White / 6500K
LED Make	Edison / Seoul / Osram/ Everlight / Bridgelux
No. of LED's	36
Lumens	550 Lm
Light Viewing Angle	300 Degree
Lamp Housing	Cylindrical Opal White PC Pipe, Polyamide based filament filled with 30% glass fibers <u>Handle</u>
Cable	2 core Round Flexible Cable 1.5 Meters Power Cord
Insulation Withstand Voltage	AC1500V / 1 Min
Avg. Life Hours	25,000 Hrs

Ordering Code

Model Number
SMC-EX-40-230

Input Voltage
230V AC / 50-60 Hz

Features —

- Modular Slim design, Light Weight & Unbreakable.
- IP 54 grade protection.
- Excellent White Light
- Opal White PC dome.
- Top Hook can be rotated 360 degrees
- Rear Hook and Magnet (Optional)
- ON-OFF switch (Optional)
- Heat Resistant and Shock Proof.
- Applications – Elevators, Escalators, Project sites, Automobile Sector, Chemical vessel manufacturers, Fabrication workshops/sites, confined spaces, etc

Dimensional Drawing —

